

MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A



OFFICE OF NAVAL RESEARCH

Contract N00014-83-K-0470-P00003

Task No. NR 359-718

TECHNICAL REPORT # 77

Recent Advances in UV-Visible Reflectance Spectroelectrochemistry

Ву

Stanley Pons, K. Ashley



Prepared for Publication in

Trends in Analytical Chemistry

University of Utah Department of Chemistry Salt Lake City, Utah 84112

July 30, 1986

Reproduction in whole or in part is permitted for any purpose of the United States Government.

This document has been approved for public release and sale; its distribution is unlimited.

REPORT DOCUMENTATION PAGE	
	READ INSTRUCTIONS HEFORE COMPLETING FORM
1. HEPORT NUMBER 2. GOVT ACCESSION N	
77	
4. TITLE (and Subissio)	5. TYPE OF REPORT & PERIOD COVERED
Recent Advances in UV-Visible Reflectance Spectroelectrochemistry	Technical Report # 77
•	6. PERFORMING ORG. REPORT HUMBER
7. AUTHOR(s)	8. CONTRACT OR GRANT NUMBER(s)
Stanley Pons, K. Ashley	N00014-83-K-0470-P0003
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROSRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
University of Utah Department of Chemistry	Task No. NR 359-718
Salt Lake City, UT 84112	
Office of News Describe	12. REPORT DATE
Office of Naval Research	July 30, 1986
Chemistry Program - Chemistry Code 472 Arlington, Virginia 22217	
Arlington, Virginia 22217 14. MONITORING AGENCY NAME & ADDRESS(II dillerent from Controlling Office)	IS. SECURITY CLASS. (of this report)
	Unclassified
	154. DECLASSIFICATION/DOWNGRADING
7. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If different in	om Report)
	·
•	And a factor of the second of
	•
18. SUPPLEMENTARY NOTES	
8. SUPPLEMENTARY NOTES	
8. SUPPLEMENTARY NOTES	
8. SUPPLEMENTARY NOTES	
18. SUPPLEMENTARY NOTES S. KEY WORDS (Continue on severce side if necessary and identify by block number	,
9. KEY WORDS (Cantinua on torsion aids if necessary and identify by block number	
W-VIS Spectroelectrochemistry, Ultraviolet	visable (
9. KEY WORDS (Cantinua an service aids if necessary and identify by block number	visable (
WW-VIS Spectroelectrochemistry, Ultraviolet ABSTRACT (Continue on reverse olds if necessary and identify by block number The technique has recently been applied to electrodes, surface adsorbed species, surface plas	visable the study of polymer modified
S. KEY WORDS (Continue on reverse side if necessary and identify by block number of the VIS Spectroelectrochemistry) Uhavioled and VIS Spectroelectrochemistry of the VIS Spectroelectrochemist	visable the study of polymer modified
The technique has recently been applied to electrodes, surface adsorbed species, surface plas	visable the study of polymer modified

Trends in Oudefleier Chaudy

RECENT ADVANCES IN UV-VISIBLE REFLECTANCE SPECTROELECTROCHEMISTRY

Kevin Ashley and Stanley Pons¹
Department of Chemistry
Henry Eyring Chemistry Building
University of Utah
Salt Lake City, Utah 84112
USA

¹To whom correspondence should be addressed.

The second secon

ABSTRACT

experiments to examine chemical processes occurring either in solution or at the electrode surface. The technique has recently been applied to the study of polymer modified electrodes, surface adsorbed species and surface plasmons, and soluble reactive organic intermediates, in addition to many other areas of general interest. Substantial improvements have been made recently in the sensitivity of the method, which allow electrochemical kinetic and mechanistic studies on very small concentrations of electrogenerated chromophores.



Acces	sion For	
NTIS	GRALI	100
DTIC	TAB	
Unann	ounced	
Justi	fication	1
}—	ibution,	
	Avail a	
Dist	Speci	
A-1		

INTRODUCTION

Conventional electrochemical methods are quite useful for kinetic studies since the rate parameters are calculated from the measured current; this quantity can be measured at extremely low magnitudes (as low as 10^{-16} amperes at ultramicroelectrodes) and hence represents a very sensitive probe for investigations of reactions. However, no molecular specific information can be obtained from the data except via the value of the reversible standard potential, a quantity which may be difficult to determine in non-ideal systems or in mixed systems: the measured current represents the sum of all the electron transfer processes occurring in the system at a given potential. The field of spectroelectrochemistry was developed to provide information on the identities and kinetics of species involved in electrochemical reactions.

The first widely practiced spectroelectrochemical technique was UV-visible spectroscopy utilizing optically transparent electrodes (OTE's) [1]. The method was used to follow the electrochemical behavior of electrogenerated species in solution. Advances in UV-visible spectroelectrochemical instrumentation have increased sensitivity to the point where it is possible to investigate monolayer amounts of material on the electrode surface solution; optical studies of this type are, however, better served by reflection infrared spectroelectrochemistry [2,3].

More recently, improvements in cell design, light sources, detectors, and noise reduction techniques have broadened the usefulness of UV-visible spectroelectrochemical techniques, and presently electrochemical applications in the UV-visible region encompass a wide variety of areas. In addition to surface studies, work in this area has given mechanistic and kinetic information for a great number of organic and inorganic compounds dissolved in both aqueous and

non-aqueous solutions. The techniques have found wide use in the important field of polymer modified electrodes, which are of interest due to their possible applications in electrocatalysis and battery technology, the study of semiconductor electrochemistry, studies of the liquid-liquid interface, and investigations of ion transport in membranes. These are but a few examples of the numerous studies being undertaken.

SPECULAR REFLECTANCE SPECTROSCOPY: INST. MENTATION AND CELL DESIGN

The spectroelectrochemical technique practiced in the authors' laboratories makes use of specular reflection of radiation from an electrode polished to a mirror finish; this may typically be a platinum disk. The main advantage of this technique over transmission cells is that electrochemistry at bulk electrodes may be studied. Thus studies pertinent to important practical phenomena are undertaken with ease: the study of surface processes such as adsorption on single crystals, electrocatalysis at bulk metals, photocurrent studies on bulk semiconductors, and corrosion reactions[4].

For obtaining spectra of electrogenerated species, the detection scheme used is known as modulated specular reflectance spectroscopy (MSRS) $\{5.6\}$. The apparatus is shown in Figure 1. In this methodology UV-visible radiation from a high throughput monochromator is focussed onto the electrode, and the reflected radiation is collected and directed to a photodetector. The electrode potential is ac modulated between two potentials E_1 and E_2 . In a study concerned with detection of a solution soluble electrogenerated species, the base potential E_1 is usually chosen such that no faradaic process occurs at the working electrode. The second potential is usually chosen so that diffusion-limited electrochemical reaction is effected, so as to generate the maximum amount of species. Since the

quantity of electrogenerated material will be modulated with the changing current (potential), the absorbance will also be ac modulated. Phase sensitive synchronous demodulation of the photodetector response leads to a signal which is proportional to the absorbance of the chromophore (vide infra). If the radiation is scanned in energy, a spectrum of the chromophore is obtained.

The cell typically used for in situ UV-visible spectroelectrochemical measurements is shown in Figure 2. The mirror disk electrode is mounted onto the end of a brass rod sheathed in an inert material such as Kei-F. The assembly is inserted into the cell through a glass barrel. Quartz windows set at a desired angle with respect to the electrode surface normal allow the radiation to pass into and after reflection pass out of the cell. A Luggin capillary reference probe is placed about Imm from the working electrode in a position that does not obstruct the optical path. A planar secondary electrode is placed opposite and parallel to the face of the working electrode; this provides reliable innear diffusion conditions across the surface of the mirror disk for as long as ten seconds:

In order to minimize noise due to extraneous light and vibrations, the cell is mounted within a light-tight black plexiglass box atop an air-cushioned optical bench. This apparatus has been used for a number of studies including studies of chemical reactions in solution processes [5-13], surface processes [14,15], and processes occurring within polymer films deposited onto electrode surfaces [16].

The reflectance experiment has additional advantages over other in s.ta UV-VIS spectroelectrochemistries than that mentioned above [13]. First, the intensity of a light beam transmitted through an OTE may be attenuated considerably relative to that reflected from the corresponding solid electrode which must result in poorer signal-to-noise ratios. Second, OTE's formed by deposition of a thin conducting film onto a transparent substrate often have very high resistances. This can lead to uneven current distribution across the surface of the OTE. Third, the reflectance technique is inherently more sensitive than the OTE technique since the light beam passes through the kinetic diffusion layer twice, thereby encountering a greater number of chromophores. Fourth, since the secondary electrode must not obstruct the light path, it is not possible in a transmission experiment to position the working electrode so that all points on its surface are equidistant from the auxiliary electrode. This leads to inhomogeneous potential distribution across the electrode surface and loss of well-defined mass transport conditions. The mathematics of mass transport has been developed only for a very few number of mass transport geometries.

Enhanced signal-to-noise ratios have recently been achieved through the use of better signal averaging techniques, more sensitive phase-sensitive detection. Fourier transform techniques, optical ac polarographic analysis, and more stable high intensity arc lamp sources. Optimized signal averaging utilizing a computer interfaced with a digital oscilloscope [10,11] has made it possible for very short transients to be obtained for species with low extinction coefficients. Arc lamps utilizing optical feedback through a photodiode have enhanced throughput and stability by increasing intensity and reducing flicker. Fiber optics have been used for both detection and as sources, and work in this area continues. Lasers have also proven to be very useful in many cases. With the incorporation of photodiode array detectors and charge coupled devices (CCD), spectral and transient data (time resolved spectra) can be obtained simultaneously [12], and the temporal behavior of several species of interest can

be followed with greater ease and speed. Sinusoidally modulated AC reflectance spectroscopy (SMACRS) [13] has increased electrochemical sensitivity manyfold by eliminating contributions to the electrochemical response due to charging current: the charging current has no inherent spectral response. Maximization of throughput and signal coupled with the minimizing of noise have made UV-visible spectroelectrochemistry one of the most powerful electroanalytical techniques.

Experiments are usually carried out in two stages. First, one obtains spectra of the species of interest by the MSRS technique. For optimum signal-to-noise ratios, the electrode potential is square wave modulated as previously described at a suitably high frequency and the amplitude of the normalized reflectance

$$\Delta R/R = (R(E_2) - R(E_1)) \wedge R(E_1)$$

is monitored as a function of wavelength. This quantity is related to the absorbance A by the relation

$$A = \ln (\Delta R R - 1)$$

A lock-in amplifier and frequency filter (Figure 1) are used to measure the fundamental harmonic ac reflectance signal from the photodetector tube with respect to the applied potential modulation frequency (usually 40-80 Hz). This corresponds to ΔR . This signal must then be ratioed to the dc value of the intensity of the reflectance $R(E_1)$. This may be done automatically by driving the photodetector at constant gain across the spectrum, or by using an electronic divider circuit, or division with the computer controller. Absorption bands with

negative $\Delta R/R$ values correspond to species present at the stepped potential E_2 . while positive $\Delta R/R$ bands are due to absorbing species at the base potential E_1 . In this way a spectrum of reactants, intermediates, and products of a given electrode reaction sequence can be obtained.

The second stage of the experiment is to investigate the kinetics of the formation/decay of the species of interest. This is most conveniently accomplished by measuring optical transients at pertinent wavelengths. Here, the optical response to a potential step is digitally recorded. Since a single transient signal is very weak, the signal-to-noise ratio is likely to be too poor for analysis. This problem is usually overcome by signal averaging techniques. The important criterion to consider here is the recovery of the diffusion kinetic layer to relax to its original condition before recording subsequent transients. This relaxation may be expedited by automatic stirring cycles after each potential step excursion. The absorbance response recorded is related to double potential step chronocoulometry [17], and the mathematics associated with this technique can be used to describe the spectroelectrochemical response. technique is suited both to the study of heterogeneous and homogeneous reaction rate parameters [7,8]. The specificity of the technique makes this methodology ideally suitable for resolving ambiguities in interpretation of current potential-time measurements in these often complicated systems

<u>APPLICATIONS</u>

SOLUTION PROCESSES

most common application of reflectance spectroelectrochemistry is the study of electrogenerated intermediates that are soluble in the bulk solution

An example of such a spectrum is that for one of the classic electrochemical "model" systems, the reduction of 9.10-diphenylanthracene in acetonitrile (Figure 3). As a point of interest, spectroelectrochemical data proved that the system is not simple at a platinum electrode: the reaction instead involves hydrogen which is sorbed into the platinum metal which is first reduced to hydride. The hydride ion in turn reacts with diffusing diphenylanthracene at a faster rate than heterogeneous electron transfer [5]. The spectrum at long wavelengths (negative values of absorbance) corresponds to that of the solution stable anion radical, while the band going positive at about 400nm corresponds to the spectrum of neutral diphenylanthracene, which is being consumed.

Representative transients for a system composed of a highly strained hydrocarbon and oxygen are shown in Figure 4 [10]. In the absence of oxygen (Figure 4a), the neutral molecule gives rise upon reduction to a long-lived anion radical; this transient corresponds to the formation of a stable ion radical; the couple is electrochemically reversible, and the reaction is a simple one-electron transfer. When oxygen is present in solution, the anion radical reacts with 0_2 , giving rise to the transient seen in Figure 4b. Notice the rapid fall-off of absorbance at the end of the applied potential pulse. Here transient spectroelectrochemical data gives mechanistic information which is unavailable from conventional voltammetric experiments.

In a similar study [11] the rate constant for the decay of a quasi-stable cation radical of a strained hydrocarbon was computed using a transient technique. At short times the cation radical is formed at a diffusion-limited rate. At long enough times, however, cation reaction occurs due to a chemical side reaction, and the expected absorbance due to the radical is less than would be expected. Figure 5 shows plots of $-\Delta R/R/VS$, $t^{1/2}$ for this system. From this

data the rate constant for the decay of the rankal intermediate (assuming first-order or pseudo-first order kinetics) was completed from [9]

$$k = \frac{\left[-\Delta R R\right]_0 - \left[\Delta R R\right]_k}{\int_0^t \left[-\Delta R R\right]_k dt}$$

where $[-\Delta R/R]_0$ is the change in reflectance which would be obtained at time t if the absorbing species did not decay, and $[-\Delta R/R]_k$ is the change in reflectance where decay occurs with a first order rate constant k. In this way, kinetic data for a homogeneous process involving a reactive intermediate can be easily obtained, while such information is oftentimes difficult to abstract from voltammetric data, especially for fast processes.

SURFACE PROCESSES

Ellipsometry is a routinely used technique for the study of films on electrode surfaces. For the electrochemist, however, this method is expensive and slow, and has consequently been used primarily for the obtaining of optical constants of films on electrode surfaces. As a result, techniques based on the monitoring of the electroreflectance effect at the electrode solution interface have been developed. A polarized monochromatic beam is focussed on the electrode surface at a known angle of incidence and the intensity of the reflected beam is recorded as a function of wavelength, angle, potential, or time. The reflectivity of the metal will change as a function of potential due to the change in the population of conduction electrons in the surface of the electrode. The data are then compared to model calculations based on Fresnel's equations using the same three layer optical model that is used in ellipsometry, i.e. the electrode interfacial region, bulk solution.

Recently, reflectance methods have been used to examine underpotential deposition of copper onto platinum [14]. The dependence of $\Delta R/R$ on the coverage of adsorbed Cu atoms on a Pt crystal was examined as a function of crystal surface $\{(100)\ vs.\ (111)\ vs.\ (110)\}$. The results suggested that adsorption occurs preferentially along the (110) face, and the workers presented microspecific information on the preferential locations of adsorbed atoms as a function of coverage. This study clearly demonstrated the utility of reflectance experiments to detailed surface analysis.

The technique has been used to study surface plasmons [15]. Surface plasmons are longitudinal electromagnetic waves that propagate at the interface between a metal and a dielectric. Internally reflected radiation may be used to induce the plasmon at a precise angle of incidence. A laser source is usually used and the angle of incidence scanned until a sharp decrease in reflectivity is observed. This method has been used to study double layer effects and adsorption. Surface plasmon spectroscopy is currently being extended to investigate semiconductors and polymer modified electrode surfaces in addition to surfaces of metals.

POLYMER MODIFIED ELECTRODES

modified electrodes. In a recent study [16] MSRS spectra were recorded for a poly-paraphenylene film as a function of applied potential. The film was electrodeposited onto a platinum mirror electrode from the electrochemicality induced polymerization of biphenyl. The spectrum of the film was then taken as a function of degree of oxidation (Figure 6). It is seen that the signal increases

with potential, and indicates the generation of two all obing states on oxidation. The band at 620nm ma, be due to an excitation from the valence band to a polaron level, while the band at 380nm is attributed to band gap excitation.

Transient data for a polypyrrole film [18] on platinum film revealed that the electropolymerization reaction leading to the formation of the film was not diffusion limited. These data suggest a radical coupling reaction controlling the electropolymerization. Chronoabsorptometric data gave estimates of diffusion coefficients within the films, and also provided information on film structure.

CONCLUDING REMARKS AND FUTURE DEVELOPMENTS

We have recently undertaken studies which involve the coupling of spectral and transient UV-VIS reflection techniques with conventional electrochemical methods such as complex plane impedance analysis and FTIR spectroelectrochemistry. New information regarding the dynamical and structural character of the electrochemical interface can be obtained from this data. Surface imaging via Raman scattering and high resolution FTIR microscopy will provide correlations between reaction rates and surface morphology. UV-visione spectroelectrochemical methods continue to be used routinely for the study of solution electrode processes, and is an important tool for the determination of mechanistic and kinetic aspects of electron transfer reactions. Work has been undertaken on the application of the technique to reactions at microelectrode arrays [19]: results provide information regarding reactions not restricted to mass transfer effects, ie steady state measurements under steady state conditions

LITERATURE REFERENCES

- 1. N. Winograd, H.N. Blount, and T. Kuwana, <u>J. Phys. Chem.</u> 73 (10), 3456 (1969).
- 2. K. Ashley and S. Pons. Trends Anal. Chem. 4(6), 142 (1985).
- 3. J.K. Foley and S. Pons. Anal. Chem. 57 945A (1985).
- 4. Southampton Electrochemistry Group, <u>Instrumental Methods in Electrochemistry</u>. T.J. Kemp. Ed., Wiley, Chichester, U.K. (1985).
- 5. A. W. Almer-Kelly, A. Bewick, P.R. Cantrell, and A. M. Tuxford, <u>Discuss</u>.

 Faraday Soc. 56, 96,(1973).
- S. Pons and S.B. Khoo, <u>J. Am. Chem. Soc.</u> <u>104</u>, 3845 (1982), and
 A. Bewick, G.J. Edwards, J.M. Mellor and S. Pons, <u>J.C.S. Perkin II</u>, 1952 (1977).
- 7. B. Speiser, A. Reiker and S. Pons. J. Electroanal. Chem. 159, 63 (1983).
- 8. A. Bewick, J.M. Mellor and S. Pons, Electrochim. Acta 25, 931 (1983).


9. S.B. Khoo, Ph.D. Thesis, University of Alberta (1984).


- 10. K. Ashley, J.K. Foley, Q. Mei, J. Ghoroghchian, F. Sarfarazi, J. Cassidy, B. Halton, P.J. Stang and S. Pons, J. Org. Chem., in press.
- 11. K. Ashley, F. Sarfarazi, S.J. Buckland, J.K. Foley, Q. Mei, B. Halton, P.J. Stang and S. Pons. Analyt Chim. Acta, submitted for publication.
- 12. L.A. Bottomley, M.R. Deakin and J.-N. Gorce, Inorg. Chem. 23, 3563 (1984).
- 13. A.S. Hinman, J.F. McAleer and S. Pons, J. Electroanal, Chem. 154, 45 (1983).
- 14. D.M. Kolb, R. Kotz and K. Yamamoto, Surf. Sci. 87, 20 (1979).
- 15. A. Otto, Surf. Sci. 101, 99 (1980).

- 16. J.F. McAleer, K. Ashley, J.J. Smith, S. Bandyopadhyay, J. Ghoroghchian, E.M. Eyring, S. Pons, H.B. Mark and G. Dunmore, J. Molec. Electron., in press.
- 17. J.H. Christie, R.A. Osteryoung and F.C. Anson, <u>J. Electroanal</u>, Chem. 13, 236 (1967).
- 18. E.M. Genies, G. Bidan and A.F. Diaz. J. Electroanal. Chem. 149, 101 (1983).
- 19. J. Cassidy, Ph.D. Thesis, University of Utah (1985).


FIGURE LEGENDS


- Figure 1. MSRS experimental arrangement.
- Figure 2. MSRS kinetic cell.
- Figure 3. (a) MSRS spectrum of $1.0m\underline{M}$ 9.10-diphenylanthracene at a vitreous carbon electrode (in acetonitrile tetrabutylammonium tetrafluoroborate $(0.1\underline{M})$, modulation frequency = 40Hz, step 0.00 to -2.50V vs. Ag Ag).
 - (b) Same spectrum made at a platinum mirror electrode.
- Figure 4. (a) Reflectance spectroscopic transient for the absorbance of the anion radical of 1-diphenyl methylene cyclopropa(b)napthalene (ImM in acetonitril): 0.1M tetrabutylammonium tetrafluoroborate potential ste -1.00 to -2.10 V vs. Ag.Ag., \(\lambda=519nm\)) The solution is oxy, n free.
 - (b) Same parameters as (a), except that oxygen is present.
- Figure 5. Reflectance vs. square root of time plot for the formation of the cation radical of 1.1-diphenylmethylenecyclopropabenzene from transients of duration: +20ms: 40ms: 100ms: x 200ms: o 400ms. Solution is 1mM in hydrocarbon in acetonitrile .1M TBAF. >-473nm Potential step 0.00 to +0.90V vs. Ag Ag⁻.
- Figure 6. MSRS spectra of poly-paraphenylene film grown potentiostatically at 1.3V vs. Ag/Ag^{-} . The applied potential was (a) 0-200mV (b) 200-400mV and (c) 400-600mV at a frequency of 80Hz.







The optical cell configuration used for modulated reflectance experiments











DL/413/83/01 GEN/413-2

TECHNICAL REPORT DISTRIBUTION LIST, GEN

<u>c</u>	No. opies		No. Copies
Office of Naval Research Attn: Code 413 800 N. Quincy Street Arlington, Virginia 22217	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 5042 Crane, Indiana 47522	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Commander, Naval Air Systems Command Attn: Code 310C (H. Rosenwasser) Washington, D.C. 20360	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	:
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko Port Hueneme, California 93401	1	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 2770	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 1911	1.2
DTNSRDC Attn: Dr. G. Bosmajian Applied Chemistry Division Annapolis, Maryland 21401	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1
Dr. William Toiles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375	1		

Dr. Paul Delahay Department of Chemistry New York University New York, New York 10003

Dr. P. J. Hendra
Department of Chemistry
University of Southampton
Southampton S09 5NH
United Kingdom

Dr. J. Driscoll Lockheed Palo Alto Research Laboratory 3251 Hanover Street Palo Alto, California 94304

Dr. D. N. Bennion
Department of Chemical Engineering
Brigham Young University
Provo, Utah 84602

Dr. R. A. Marcus Department of Chemistry California Institute of Technology Pasadena, California 91125

Dr. J. J. Auborn
Bell Laboratories
Murray Hill, New Jersey 07974

Dr. Joseph Singer, Code 302-1 NASA-Lewis 21000 Brookpark Road Cleveland, Ohio 44135

Dr. P. P. Schmidt
Department of Chemistry
Oakland University
Rochester, Michigan 48063

Dr. Manfred Breiter Institut fur Technische Elektrochemie Technischen Universitat Wien 9 Getreidemarkt, 1160 Wien AUSTRIA Dr. E. Yeager Department of Chemistry Case Western Reserve University Cleveland, Ohio 44106

Dr. C. E. Mueller
The Electrochemistry Branch
Naval Surface Weapons Center
White Oak Laboratory
Silver Spring, Maryland 20910

Dr. Sam Perone
Chemistry & Materials
Science Department
Lawrence Livermore National Laboratory
Livermore, California 94650

Dr. Royce W. Murray
Department of Chemistry
University of North Carolina
Chapel Hill, North Carolina 27514

Dr. B. Brummer EIC Incorporated 111 Downey Street Norwood, Massachusetts 02062

Dr. Adam Heller Bell Laboratories Murray Hill, New Jersey 07974

Dr. A. B. Ellis Chemistry Department University of Wisconsin Madison, Wisconsin 53706

Library
Duracell, Inc.
Burlington, Massachusetts 01803

Electrochimica Corporation 20 Kelly Court Menlo Park, California 94025-1418

Dr. M. Wrighton Chemistry Department Massachusetts Institute of Technology

Cambridge, Massachusetts 02139

Dr. B. Stanley Pons Department of Chemistry University of Utah Salt Lake City, Utah 84112

Donald E. Mains Naval Weapons Support Center Electrochemical Power Sources Division Crane, Indiana 47522

S. Ruby DOE (STOR) Room 5E036 Forrestal Bldg., CE-14 Washington, D.C. 20595

Dr. A. J. Bard Department of Chemistry University of Texas Austin, Texas 78712

Dr. Janet Osteryoung Department of Chemistry State University of New York Buffalo, New York 14214

Dr. Donald W. Ernst Naval Surface Weapons Center Code R-33 White Oak Laboratory Silver Spring, Maryland 20910

Mr. James R. Moden Naval Underwater Systems Center Code 3632 Newport, Rhode Island 02840

Dr. Bernard Spielvogel U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709

Dr. Aaron Fletcher Naval Weapons Center Code 3852 China Lake, California 93555 Dr. M. M. Nicholson Electronics Research Center Rockwell International 3370 Miraloma Avenue Anaheim, California

Dr. Michael J. Weaver Department of Chemistry Purdue University West Lafayette, Indiana 47907

Dr. R. David Rauh EIC Laboratories, Inc. 111 Downey Street Norwood, Massachusetts 02062

Dr. Aaron Wold Department of Chemistry **Brown University** Providence, Rhode Island 02192

Dr. Martin Fleischmann Department of Chemistry University of Southampton Southampton SO9 5NH ENGLAND

Dr. R. A. Osteryoung Department of Chemistry State University of New York Buffalo, New York 14214

Dr. John Wilkes Air Force Office of Scientific Research Bolling AFB Washington, D.C. 20332

Dr. R. Nowak Naval Research Laboratory Code 6171 Washington, D.C. 20375

Dr. D. F. Shriver Department of Chemistry Northwestern University Evanston, Illinois 60201

Dr. Hector D. Abruna
Department of Chemistry
Cornell University
Ithaca. New York 14853

Dr. A. B. P. Lever Chemistry Department York University Downsview, Ontario M3J1P3

Dr. Stanislaw Szpak Naval Ocean Systems Center Code 633, Bayside San Diego, California 95152

Dr. Gregory Farrington
Department of Materials Science
and Engineering
University of Pennsylvania
Philadelphia, Pennsylvania 19104

M. L. Robertson
Manager, Electrochemical
and Power Sources Division
Naval Weapons Support Center
Crane, Indiana 47522

Dr. T. Marks
Department of Chemistry
Northwestern University
Evanston, Illinois 60201

Dr. Micha Tomkiewicz Department of Physics Brooklyn College Brooklyn, New York 11210

Dr. Lesser Blum Department of Physics University of Puerto Rico Rio Piedras, Puerto Rico 00931

Dr. Joseph Gordon, II IBM Corporation 5600 Cottle Road San Jose, California 95193

Dr. Nathan Lewis Department of Chemistry Stanford University Stanford, California 94305 Dr. D. H. Whitmore Department of Materials Science Northwestern University Evanston, Illinois 60201

Dr. Alan Bewick Department of Chemistry The University of Southampton Southampton, SO9 5NH ENGLAND

Dr. E. Anderson NAVSEA-56Z33 NC #4 2541 Jefferson Davis Highway Arlington, Virginia 20362

Dr. Bruce Dunn
Department of Engineering &
Applied Science
University of California
Los Angeles, California 90024

Dr. Elton Cairns
Energy & Environment Division
Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

Dr. Richard Pollard Department of Chemical Engineering University of Houston Houston, Texas 77004

Dr. M. Philpott IBM Corporation 5600 Cottle Road San Jose, California 95193

Dr. Donald Sandstrom Boeing Aerospace Co. P.O. Box 3999 Seattle, Washington 98124

Dr. Carl Kannewurf
Department of Electrical Engineering
and Computer Science
Northwestern University
Evanston, Illinois 60201

Dr. Joel Harris
Department of Chemistry
University of Utah
Salt Lake City, Utah 84112

ነዋልና በብር የመመመለው የመመመ የሚያስተው የመመመር የመንከር የመንከር

Dr. Robert Somoano Jet Propulsion Laboratory California Institute of Technology Pasadena, California 91103

Dr. Johann A. Joebstl
USA Mobility Equipment R&D Command
DRDME-EC
Fort Belvoir, Virginia 22060

Dr. Judith H. Ambrus NASA Headquarters M.S. RTS-6 Washington, D.C. 20546

Dr. Albert R. Landgrebe U.S. Department of Energy M.S. 68025 Forrestal Building Washington, D.C. 20595

Dr. J. J. Brophy
Department of Physics
University of Utah
Salt Lake City, Utah 84112

Dr. Charles Martin Department of Chemistry Texas A&M University College Station, Texas 77843

Dr. H. Tachikawa Department of Chemistry Jackson State University Jackson, Mississippi 39217

Dr. Theodore Beck Electrochemical Technology Corp. 3935 Leary Way N.W. Seattle, Washington 98107

Dr. Farrell Lytle
Boeing Engineering and
Construction Engineers
P.O. Box 3707
Seattle, Washington 98124

Dr. Robert Gotscholl U.S. Department of Energy MS G-226 Washington, D.C. 20545 Dr. Edward Fletcher Department of Mechanical Engineering University of Minnesota Minneapolis, Minnesota 55455

Dr. John Fontanella Department of Physics U.S. Naval Academy Annapolis, Maryland 21402

Dr. Martha Greenblatt
Department of Chemistry
Rutgers University
New Brunswick, New Jersey 08903

Dr. John Wasson Syntheco, Inc. Rte 6 - Industrial Pike Road Gastonia, North Carolina 28052

Dr. Walter Roth
Department of Physics
State University of New York
Albany, New York 12222

Or. Anthony Sammells Eltron Research Inc. 4260 Westbrook Drive, Suite 111 Aurora, Illinois 60505

Dr. C. A. Angell Department of Chemistry Purdue University West Lafayette, Indiana 47907

Dr. Thomas Davis
Polymer Science and Standards
Division
National Bureau of Standards
Washington, D.C. 20234

Ms. Wendy Parkhurst Naval Surface Weapons Center R-33 R-33 Silver Spring, Maryland 20910

Dr. John Owen
Department of Chemistry and
Applied Chemistry
University of Salford
Salford M5 4WT ENGLAND

Dr. Boone Owens
Department of Chemical Engineering
and Materials Science
University of Minnesota
Minneapolis, Minnesota 55455

Dr. J. O. Thomas University of Uppsala Institute of Chemistry Box 531 S-751 21 Uppsala, Sweden Dr. O. Stafsudd Department of Electrical Engineering University of California Los Angeles, California 90024

Dr. S. G. Greenbaum Department of Physics Hunter College of CUNY New York, New York 10021

Dr. Menahem Anderman W.R. Grace & Co. Columbia, Maryland 20144

END DATE
FILMED 6-1988 DTic